

SoloSound PET

Specification Text

This acoustic range comes with a PET felt backing layer which provides for an excellent acoustic performance. The timber laths come on a veneered MDF and can be made to suit bespoke dimensions and specific requirements.



Type	Burke Acoustics SoloSound PET
Flat Surface width	24,0mm
Groove width	12,0mm
Core/substrate	MDF / MDF Fire Rated / MDF Black Coloured / Plywood
Edges	Industrial saw cut
Felt Colour	Standard Black, other colours on request (MoQ)
Felt Thickness	9mm
Panel Thickness	27mm
Dimensions	Standard: 2400mm x 600mm

SoloSound PET

Surface	HPL / CPL, Ash Veneer, White Oak Veneer, Maple Veneer, Walnut Veneer, Lacquer		
Surface treatment	Lacquered Matt (25% sheen), Dull Matt (10% sheen), Transparent (veneer only)		
Veneer Direction	Along length		
Joints	1 – 50mm		
Installation System	<i>Planks:</i> Hardened high tensile stainless steel clip fixing Galvanized Steel profile rails to hang in panels		
Fire behaviour	D-s3,d2 (normal flammability) B-s2,d0		
Acoustics absorption	<i>Built up</i>	<i>57mm</i>	<i>57mm</i>
	Cavity	30mm	30mm
	Wool	30mm	0mm
	Panel thickness	27mm	27mm
	Alpha w	0,95	0,65
	NRC	0,90	0,75
	SAA	0,90	0,76
	Class	A	C
	DoP	Available	