



# ProSound 8-8-1.5

The ProSound product line offers high performing sound absorption capabilities through a multitude of different sized holes. This panel system can be used on both wall and ceiling applications.

The range is available with varying perforated surfaces such as 1,5mm, 2mm, 3mm, 5mm, 6mm or 8mm holes. The functionality of this product allows for various sheet size finishes to allow flexibility for the end user. This product is available in a range of real wood veneers, CPL and paint finishes.

Hole Diameter: 1,5mm  
 Distance hole center: 8mm/8mm  
 Non Perforated Frame: 20mm

## Fire Behaviour:

D-S3,d2 (normal flammability)  
 B-s1,d0 (Veneer, lacquer)  
 B-s2,d0 (laminated)  
 A2-s1,d0 (Veneer, microlaminated)

## Surfaces:

HPL/CPL, Veneer, Lacquer

## Open Surface:

2,7%

## Temperature/Rel Humidity Range

15-25 °C and 45-60%

## Dimensions

Standard: length 2760mm  
 width 1300mm  
 thickness 17mm  
 Maximum length 3500mm (Gypsum Fiber 3050mm)  
 width 1300mm

Built up	69mm		
Cavity	20mm		
Wool	30mm		
Panel thickness	19mm		
Alpha w	0,33		
NRC	0,60		
SAA	0,60		

