

# LinearSound-Split

## Specification Text

This Linear product line offers an economical price to performance ratio. This panel system can be used on both wall and ceiling applications. The grooves can be in a multiple of different widths that include: 2mm through to 4mm wide with different spacing of the groove to offer regulated lines or irregular positions.



Type	Burke Acoustics LinearSound Split
Flat Surface width	Irregular
Groove width	3, 0mm
Core/substrate	MDF / MDF Fire Rated / MDF Black Coloured / Plywood
Edges	<i>Long side:</i> Industrial saw cut, tongue and groove profile <i>Head ends:</i> Industrial saw cut <i>Ceiling tile:</i> for T15 and T24 Grids
Acoustic felt	Black (not visible)
Thickness	16mm - 20mm

# LinearSound-Split

Dimensions	Standard: 2780mm x 128mm to 1200mm Maximum: 3000mm x 1200mm																												
Surface	HPL / CPL, Veneer, Melamine, Lacquer (RAL/NCS), Digital Print																												
Surface treatment	Lacquered Matt (25% sheen), Dull Matt (10% sheen), Transparent (veneer only)																												
Veneer Direction	Along length																												
Joints	<i>Tongue &amp; Groove edge: Closed 0mm</i> <i>Head ends: 1-2mm</i>																												
Installation System	<i>Planks: Hardened high tensile stainless steel clip fixing</i> Galvanized Steel profile rails to hang in panels																												
Fire behaviour	D-s3,d2 (normal flammability) B-s1,d0 (Veneer, Lacquer) B-s2,d0 (Laminate) A2-s1,d0 (Microlaminate, veneer, lacquer)																												
Acoustics absorption	<table><tr><td><i>Built up</i></td><td><i>46mm</i></td><td><i>216mm</i></td><td><i>416mm</i></td></tr><tr><td>Cavity</td><td>0mm</td><td>150mm</td><td>350mm</td></tr><tr><td>Wool</td><td>30mm</td><td>50mm</td><td>50mm</td></tr><tr><td>Panel thickness</td><td>16mm</td><td>16mm</td><td>16mm</td></tr><tr><td>Alpha w</td><td>0,58</td><td>0,62</td><td>0,63</td></tr><tr><td>NRC</td><td>0,80</td><td>0,75</td><td>0,70</td></tr><tr><td>SAA</td><td>0,77</td><td>0,74</td><td>0,70</td></tr></table>	<i>Built up</i>	<i>46mm</i>	<i>216mm</i>	<i>416mm</i>	Cavity	0mm	150mm	350mm	Wool	30mm	50mm	50mm	Panel thickness	16mm	16mm	16mm	Alpha w	0,58	0,62	0,63	NRC	0,80	0,75	0,70	SAA	0,77	0,74	0,70
<i>Built up</i>	<i>46mm</i>	<i>216mm</i>	<i>416mm</i>																										
Cavity	0mm	150mm	350mm																										
Wool	30mm	50mm	50mm																										
Panel thickness	16mm	16mm	16mm																										
Alpha w	0,58	0,62	0,63																										
NRC	0,80	0,75	0,70																										
SAA	0,77	0,74	0,70																										
DoP	Available																												